

Technical Specifications:

<b>Model</b>	<b>MRS</b>	<b>MRS-I 50</b>	<b>MRB</b>	<b>MRB-250</b>	<b>MSM</b>
<b>Test Loads (Kgf)</b>	60, 100, 150 (Rockwell)	60, 100, 150 (Rockwell)	60, 100, 150 (Rockwell) 187.5 (Brinell)	60, 100, 150 (Rockwell) 187.5, 250 (Brinell)	60, 100, 150 (Rockwell) 15, 30,45 (Rockwell Superficial)
<b>Initial Loads (Kgf)</b>	10	10	10	10	10(Rockwell)and 3 (Rockwell superficial)
<b>Max. Test Height (mm)</b>	215	295	215	295	295
<b>Depth of Throat(mm)</b>	132	148	132	148	148
<b>Max. Depth of Elevating Screw Below Base (mm)</b>	230	295	230	295	295
<b>Size of Base (mm) (Approx.)</b>	430 X 180	475 X 220	430 X 180	475 X 220	475 X 220
<b>Machine Height (mm)</b>	635	865	635	865	865
<b>Nett Weight kg (Approx.)</b>	65	105	70	125	125

Standard Accessories:

<b>Model</b>	<b>MRS</b>	<b>MRS-150</b>	<b>MRB</b>	<b>MRB-250</b>	<b>MSM</b>
Rockwell Diamond Indentor	1 No.	1 No.	1 No.	1 No.	1 No.
Superficial Diamond Indentor	-	-	-	-	1 No.
Testing Table (Ø 50 mm)	1 No.	1 No.	1 No.	1 No.	1 No.
Testing Table (Ø 40 mm with &lsquo; V" Groove for round Jobs Ø 6 to45 mm	1 No.	1 No.	1 No.	1 No.	1 No.
Steel Ball Indentor Ø1/16&rdquo;	1 No.	1 No.	1 No.	1 No.	1 No.
Steel Ball Indentor Ø 2.5 mm	-	-	1 No.	1 No.	-
Steel Ball Indentor Ø 5 mm	-	-	-	1 No.	-
Test Block HRC	1 No.	1 No.	1 No.	1 No.	1 No.
Test Block HRB	1 No.	1 No.	1 No.	1 No.	1 No.
Test Block HB 2.5 mm / 187.5 Kgf	-	-	1 No.	1 No.	-
Test Block Rockwell Superficial 30N	-	-	-	-	1 No.
Steel Ball Ø 1/16& rdquo;	5 Nos.	5 Nos.	5 Nos.	5 Nos.	5 Nos.
Allen Spanners	3 Nos.	3 Nos.	3 Nos.	3 Nos.	3 Nos.
Clamping Device	1 No.	1 No.	1 No.	1 No.	1 No.
Brinell Microscope	-	-	1 No.	1 No.	-
PVC Cover for Machine	1 No.	1 No.	1 No.	1 No.	1 No.
Rubber Bellow	1 No.	1 No.	1 No.	1 No.	1 No.
Instruction Manual	1 Book	1 Book	1 Book	1 Book	1 Book