

DUAL LINE PUMP



This system supplies lubricant to various bushes and bearings located at different parts of the machines used in steel mills, sugar plants, port & yard handling equipments, rolling mills, cement plants etc. This system consists of the following

- ⇒ Electrically operated pump with reservoir.
- ⇒ Reversing valve
- ⇒ Dual line Distributors
- ⇒ Control unit
- ⇒ Two main lines with the appropriate secondary lines and fittings.



Part List

1. Base Plate
2. Electric Geared Motor
3. Automatic Grease Pump
4. Line Change-Over Valve
5. Reservoir
6. Tell-Tale Rod
7. Limit Switch
8. Filling Filter
9. Control Panel

Pump Type	Plunger Pump
Capacity	150cc/min Model - SVM6915 250cc/min Model - SVM6925 500cc/min Model - SVM6950
Maximum Pressure	400 bar
Worm Ratio	20:1
Reservoir	70 Litres – Std 100 Litres
Motor detail	1.1 Kw, 1440 RPM, 440 V, 3 Ph, TEFC

S.V.A Rikkon Lube Pvt.Ltd

203, Nageswara Rao Road, 2nd Extn, Athipet, Chennai- 600 058.

Tel : 91-44-262558880 / 81 Fax : 91-44-26245128

Email: sales@rikkonlube.com